





Powered by the NEW IntelliCold® touch screen controller, this pharmacy refrigerator is packed with extra functions designed to store temperature sensitive pharmaceuticals in optimum conditions. It also features a 1.6 metre secondary (wandering) temperature probe that can be placed anywhere inside the fridge.



The touch screen controller is completely at so can be thoroughly cleaned and disinfected as there are no raised buttons to collect dirt and germs. The controller displays, alarms and records minimum and maximum temperatures for both temperature probes. Like a mobile phone touch screen it locks after 30 seconds to ensure that buttons can't be activated accidently.

For extra security, there is a digital lock version RLDF1019DIGLOCK which solves the problem of generic keys, but whatever the preferred model, for a small additional cost we can provide a manufacturers' calibration certificate from our in house UKAS temperature calibration laboratory No:8898.

We are con dent that this pharmacy refrigerator will provide you with many years of fault free service. However, for extra peace of mind your RLDF1019 comes complete with a 12 Months parts and labour warranty.





While you're registering your warranty, why not purchase a micro SD card and adapter for transferring data recorded by the controller from the fridge to your computer at half price?

The IntelliCold® controller records alarm states, fridge operation, door openings and temperature data for both probes at minute intervals. You can only view and store this data on a computer by purchasing a specially encoded micro SD card from Labcold. This data helps you with record keeping and regulatory inspections, plus if you have an issue, you can establish the exact duration and severity of the event.

RLDF1019 Pharmacy & Vaccine Refrigerator

Capacity (Litres)340StyleFree StandingExterior Dimensions (HxWxD)1510 x 600 x 700mmInterior Dimensions (HxWxD)1358 x 480 x 500mmTemperature Range+2.°C to +8.°COperating Temperature+5.°CPower Consumption Kwh/24hrs1.52Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Mains Failure Alarm✓Mains Failure Alarm✓Mains Failure Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling Remote Alarm Contacts✓H Green Book Guidelines✓	Part Number	RLDF1019
Exterior Dimensions (HxWxD)1510 x 600 x 700mmInterior Dimensions (HxWxD)1358 x 480 x 500mmTemperature Range+2.°C to +8.°COperating Temperature+5.°CPower Consumption Kwh/24hrs1.52Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Second Temperature Probe O Cycle Auto Defrost✓Fan Assisted Cooling Remote Alarm Contacts✓Access Port✓	Capacity (Litres)	340
(HxWxD)1510 x 600 x 700mmInterior Dimensions (HxWxD)1358 x 480 x 500mmTemperature Range+2.°C to +8.°COperating Temperature+5.°CPower Consumption Kwh/24hrs1.52Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidBoor Hingingreversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Mains Failure Alarm✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓	Style	Free Standing
(HxWxD)1358 x 480 x 500mmTemperature Range+2°C to +8°COperating Temperature+5°CPower Consumption Kwh/24hrs1.52Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidBoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓	(HxWxD)	1510 x 600 x 700mm
Operating Temperature+5₀CPower Consumption Kwh/24hrs1.52Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling Remote Alarm Contacts✓Access Port✓		1358 x 480 x 500mm
Power Consumption Kwh/24hrs1.52Interior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling Remote Alarm Contacts✓Access Port✓	Temperature Range	+2₀C to +8₀C
Kwh/24hrsInterior ConstructionPowder Coated SteelExterior ConstructionPowder Coated SteelShelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling Remote Alarm Contacts✓Access Port✓	Operating Temperature	+5₀C
Exterior ConstructionPowder Coated SteelShelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓		1.52
Shelves6Net Weight (kg)79Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling Remote Alarm Contacts✓Access Port✓	Interior Construction	Powder Coated Steel
Net Weight (kg)79Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm Alarm Battery Back-Up✓Second Temperature Probe O Cycle Auto Defrost✓Fan Assisted Cooling Remote Alarm Contacts✓	Exterior Construction	Powder Coated Steel
Internal Drawers Available✓Internal Drawers Available✓Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓	Shelves	6
Door StyleSolidDoor HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓	Net Weight (kg)	79
NorrRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum✓Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓	Internal Drawers Available	✓
Door HingingRight (can be reversed at time of manufacture)Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum✓Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓	Door Style	
Self Closing Door ✓ Key Lock ✓ Digital Temperature Control ✓ Digital Temperature Display ✓ Internal Light ✓ High/Low Temperature Alarm ✓ Minimum/Maximum ✓ Temperature Recording ✓ Automatic Temperature & Fridge Operation Data Recording ✓ Door Open Alarm ✓ Mains Failure Alarm ✓ Alarm Battery Back-Up ✓ Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Access Port ✓		
Self Closing Door✓Key Lock✓Digital Temperature Control✓Digital Temperature Display✓Internal Light✓High/Low Temperature Alarm✓Minimum/Maximum✓Temperature Recording✓Automatic Temperature & Fridge Operation Data Recording✓Door Open Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓	Door Hinging	
Key LockDigital Temperature ControlDigital Temperature DisplayInternal LightInternal LightHigh/Low Temperature AlarmMinimum/MaximumImperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmMains Failure AlarmImage: Alarm Battery Back-UpSecond Temperature ProbeO Cycle Auto DefrostFan Assisted CoolingRemote Alarm ContactsAccess Port	Solf Closing Door	manufacture)
Digital Temperature Control ✓ Digital Temperature Display ✓ Internal Light ✓ High/Low Temperature Alarm ✓ Minimum/Maximum ✓ Temperature Recording ✓ Automatic Temperature & Fridge Operation Data Recording ✓ Door Open Alarm ✓ Mains Failure Alarm ✓ Alarm Battery Back-Up ✓ Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Access Port ✓		
Digital Temperature Display ✓ Internal Light ✓ High/Low Temperature Alarm ✓ Minimum/Maximum ✓ Temperature Recording ✓ Automatic Temperature & Fridge Operation Data Recording ✓ Door Open Alarm ✓ Mains Failure Alarm ✓ Alarm Battery Back-Up ✓ Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Access Port ✓		√
Internal Light ✓ High/Low Temperature Alarm ✓ Minimum/Maximum ✓ Temperature Recording ✓ Automatic Temperature & Fridge Operation Data Recording ✓ Door Open Alarm ✓ Mains Failure Alarm ✓ Alarm Battery Back-Up ✓ Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Access Port ✓		
High/Low Temperature Alarm ✓ Minimum/Maximum ✓ Temperature Recording ✓ Automatic Temperature & Fridge Operation Data Recording ✓ Door Open Alarm ✓ Mains Failure Alarm ✓ Alarm Battery Back-Up ✓ Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Access Port ✓	Digital Temperature Display	✓
Minimum/Maximum Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmMains Failure Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Access Port✓	Internal Light	✓
Temperature RecordingAutomatic Temperature & Fridge Operation Data RecordingDoor Open AlarmMains Failure Alarm✓Mains Failure Alarm✓Alarm Battery Back-Up✓Second Temperature Probe✓O Cycle Auto Defrost✓Fan Assisted Cooling✓Remote Alarm Contacts✓Access Port		✓
Automatic Temperature & Fridge Operation Data Recording ✓ Door Open Alarm ✓ Mains Failure Alarm ✓ Alarm Battery Back-Up ✓ Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Remote Alarm Contacts ✓ Access Port ✓		✓
Operation Data RecordingDoor Open AlarmMains Failure AlarmMains Failure AlarmAlarm Battery Back-UpSecond Temperature ProbeO Cycle Auto DefrostFan Assisted CoolingRemote Alarm ContactsAccess Port		
Mains Failure Alarm ✓ Alarm Battery Back-Up ✓ Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Remote Alarm Contacts ✓ Access Port ✓		✓
Alarm Battery Back-Up ✓ Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Remote Alarm Contacts ✓ Access Port ✓	Door Open Alarm	✓
Second Temperature Probe ✓ O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Remote Alarm Contacts ✓ Access Port ✓	Mains Failure Alarm	✓
O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Remote Alarm Contacts ✓ Access Port ✓	Alarm Battery Back-Up	✓
O Cycle Auto Defrost ✓ Fan Assisted Cooling ✓ Remote Alarm Contacts ✓ Access Port ✓	Second Temperature Probe	√
Remote Alarm Contacts ✓ Access Port ✓		√
Remote Alarm Contacts ✓ Access Port ✓	Fan Assisted Cooling	✓
		✓
DH Green Book Guidelines	Access Port	✓
· · · · · · · · · · · · · · · · · · ·	DH Green Book Guidelines	
Compliant	Compliant	v

www.labcold.com

