

WALL CHILLER - JC



FEATURES	
Running Temperature	2°C/+6°C
Ambient Conditions	25°C - 60% RH
Colour Exterior	Stainless Steel
Colour Interior	Black Chromadek
Solid Patchends External	Stainless Steel
Solid Patchends Internal	Mirror
Standard with night blinds	
Trolley Bumpers	
Adjustable Shelves	
Self-Contained cabinets:	2m and 2.5m to be wired into an isolator

DIMENSIONS		UoM	4FT	6FT	8FT
Length	mm (External)		1270	1970	2470
	mm (Internal)		1200	1900	2400
Height	mm (External)		2050	2050	2050
	mm (Internal)		1250	1250	1250
Depth	mm (External)		1065	1065	1065
	mm (Internal)		610	610	603
Shelf Size and Quantity	Qty x W x D		4 X 1190 X 450	8 X 945 X 450	8 X 1199 X 450
Deck Tray Size and Quantity	Qty x W x D		2 X 600 X 610	2 X 950 X 610	4 X 600 X 603
Weight	Kg		280	445	540
Visual Area Front	m²		1,5	2,4	3
Total display area	m²		2,88	4,56	5,8
Footprint area	m²		1,35	2,18	2,7
Lighting	nr x watt		1 x 18W 900mm LED	2 x 18W 900mm LED	2 x 14W 900mm LED
Nr defrost in 24h	nr x 24h		6 @ 20 minutes	6 @ 20 minutes	3 @ 20 minutes

OPTIONAL EXTRAS

- Under shelf lighting
- Shelf fences
- Polony Hooks
- Pink LED Butchery lights
- Acrylic doors
- Branding

	UoM	4FT	6FT	8FT
Refrigeration capacity @ -10°C / 45°C	watt	2194	3884	5312
Refrigeration Gas Charge	Type/KG	R404a / 2.2	R404a / 1.5 X 2	R404a / 1.5 X 2
Rating power - Including heating elements	Watts	2370	2608	2970
	Amps	12,07	13,63	12,91
Evaporation tray heater	Watts	850 W	2 X 850 W	2 X 850 W
	Amps	3,7	7,4	7,4
Management Device / Thermostat	Type	Electronic Controller	Electronic Controller	Electronic Controller
Defrost Heater	nr.x watt	N/A Free Cycle Fan	N/A Free Cycle Fan	N/A Free Cycle Fan
Antimist Heater	Yes / No	No	No	No
Expansion Device	Type	Capillary Tube	Capillary Tube	Capillary Tube
Evaporator	Type	Fan Assist	Fan Assist	Fan Assist
Condenser	Type	Fan Assist	Fan Assist	Fan Assist
Compressor	Type	MBP/HBP	MBP/HBP	MBP