

MODEL EB1720SS Under Bar fridge 633 Litre Capacity

Dimensions: Height (mm): Width (mm):	FRIDGE 740 1115 610	FRIDGE (half doc 415 520 610	r) CABINET 900 1722 750	BOXED 1000 1800	Gross	:	TOTAL 633L	FRIDGE 633L	
Depth (mm):				850	Stora	ge Capacity:	Number of Shelves - 2 Shelve Size - 530mm × 600mm		١
		Coolir	ng System:	Finned Evaporator - Fan Forced		d			
					Temp Contro	erature ol:	Electronic		
					Energ	y :	Start Current – 5.02 Amps Run Current – 2.08 Amps Consumption - 3.86Kwh/24hrs		5
					Finish:		Interior - Stainless Steel base with Chromadek Sides Exterior - Stainless Steel with Rear Chromadek		
and and a second s					Feet:		Lockable Castor Wheels		
Optional Extras: Glass Doors* (with Integrated LED Lights)									
Loading								T	
20 Ft 12		40 Ft 24	40 Ft H/C 24	Tri Ax 28	Ie		er Link 36	Taut liner 36	
Weight: Unboxed - 100kg Boxed - 130kg					Climate class: 4 30°C 55%		6 Humidity	I	
H.S Code:	.S Code: 8418.50 8			Cable	Cable length: 2		-		
Footprint:	1.29m ²			Comp	liance:	COMESA / S	SADC		_
Website: www.	thefridgefacto	ory.com Facebo	ok: the fridge fac	ctory Instagra	m: the_fric	lge_factory	Twitter:	W1017 fridge factory	7
THE FRI FACTO	DGE DRY		Palfridge	(LID) – Design specification	s	ISO 9001:2015 COMPLIANT			

Confidentiality: This document contains information, which is confidential. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission in writing. If you have received this document in error, please notify Palfridge Ltd immediately by e-mail (info@palfridge.com), facsimile (+268 2 5184126) or telephone (+268 2 5184196) and thereafter return and/or destroy the document. Palfridge Ltd accepts no liability (to the fullest extent permitted by law) for information in this document, which does not relate to its official business. No contracts or official orders shall be concluded by means of this document. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE