



JUSTTM
REFRIGERATION

QUB4S/C Underbar Fridge

swing door - stainless steel door



3° to 5°C

	QUB4S/C	QUB6S/C	QUB8S/C
Doors	1.5	2.5	3.5
Height (with castors)	900mm	900mm	900mm
Width	1180mm	1780mm	2380mm
Depth	650mm/750mm	650mm/750mm	650mm/750mm
Temperature Range	2° to 6°C	2° to 6°C	2° to 6°C
Refrigerant	R134A	R134A	R134A
Internal Volume (Litres)	319	580	840

features

- Stainless Steel grade 430 satin finish no 4 for sides, top and front grid
- Galvanized Steel – Rear and Bottom
- Polyurethane foam injection insulation
- Robust top and bottom hinges
- Fully adjustable heavy duty plastic coated shelves
- Digital temperature display with high/low voltage protection
- Self-closing doors
- Robust handles on doors
- All underbars supplied with brake castors
- Dual thermopane safety glass used for glass doors
- Adjustable thermostat 2°C – 6°C
- Auto Evaporation (The condensate is evaporated, hence no need to drain)
- All models are 220V – Plug in and switch on
- Heavy duty sliding rail on sliding door models



emd equippedTM

Breakthrough technology replaces a conventional thermostat with an advanced electronic energy management system to cool quicker and maintain a more consistent temperature, while saving precious electricity.



green advantageTM

By combining EMD control with ECM fans, electronic expansion valves and high-performance coils, we are able to further reduce energy consumption while improving cooling performance.



swift swopTM

Our innovative swift swopTM technology enables easy replacement of the refrigeration deck without unpacking the contents of the fridge and without any skilled labour.



low e cabinetTM

A superior combination of LED lighting, polyurethane insulation and low emissivity glass yields power savings around 40% lower than conventional refrigeration units.