



REFRIGERATION & CATERING EQUIPMENT
MANUFACTURERS

BEE
LEVEL
2

GUARANTEED ENHANCED LIFETIME PERFORMANCE.

Economical and easily replaceable disposable filters on the condenser radiator eliminates servicing costs and guarantees integrity of the condenser for the lifetime of the fridge.

UNDERBAR QUICK FAQ REFERENCE SHEET



Filter at rear of fridge



Slide off the filter locating brackets



Remove old filter and fit new filter in reverse

DOORS:

Self-closing with Auto hold open functionality.
Magnetic clip on door gaskets.
Integrated handles welded on to Stainless steel.

LIGHTING:

Light: LED T8 Daylight white or Blue.

DIMENSIONS:

Standard Depth is 650mm, 750mm available on request.

Standard traditional lengths are 1180mm (1.5doors) , 1780mm (2.5doors) , 2380mm (3.5doors)- for STD doors 550mm.

Gastronome lengths are 1350mm (2.5doors) , 1780mm (3.5doors) , 2380mm (4.5doors)- for GN doors 460mm.

Work top Height is 900mm.

CONSTRUCTION:

Construction: 50mm laminate virgin polystyrene insulation in combination with Chromadek and Brushed 430 stainless steel.

Splashbacks - is retrofit, 100mm being the industry norm, however differing heights can be accommodated on request.

Weights: 80 to 197kg- see spec sheet.

MOBILITY:

Wheels or feet? Height adjustable feet are generally selected for uneven floors and is on request only- No cost difference.

POWER:

Nominal power requirement 375watts to 650watts@230VAC.

STORAGE

Shelving: Black powder coated mild steel wire type, height adjustable on heavy duty nylon clips.

GN variable racking system to accommodate GN1/1 are fitted into the Gastronome fridges for the following quantities per GN full door:

- GN1/1x65mm 6off
- GN1/1x100mm 4off
- GN1/1x80mm 4off
- GN1/1x150mm 3off

Raised pizza tops - includes night cover and insulation.

Number of inserts detailed below:

- 1180mm: 6x1/6th or 3x1/3rd up to 150mm depth
- 1780mm: 10x1/6th or 5x1/3rd up to 150mm depth
- 2380mm: 13x1/6th or 6x1/3rd up to 150mm depth

OPTIONS

Slide tops, Low boys, Drawers, Locking bars, Doors both sides, Material spec change 304SS etc, Dimensions, Hampers and polarwells, Sneezeguards – curved and square, Freezer.

TEMPERATURE

Minimum temperature settings: Chiller +2.0degC, **Freezer -14degC.**

Freezers: when recommending or quoting on freezers, please contact the supplier regarding expectations the client may have of the freezer; it makes sense to discuss as some clients do not realise that ice cream cannot be stored in these units.

WARRANTY

12months - refer to manual for terms and conditions.



1780 2.5 Hampers



1780 3.5 GN SS door



1780 2.5 SS door



1780 3.5 GN Glass door



2380 3.5 Glass door

METNOR UNDERBAR FRIDGE

