FUB 6S/C



underbar freezer - stainless steel door



specifications

• Doors: 2

• Height (with castors): 900mm

• Width: 1780mm

• Depth: 650mm/750mm

• Temperature Range: - 14°C

Refrigerant: R404Internal Volume: L

features

- Stainless Steel grade 430 satin finish no 4 for sides, top and front grid
- Galvanized Steel Rear and Bottom
- Polyurethane foam injection insulation
- Robust top and bottom hinges
- Fully adjustable heavy duty plastic coated shelves
- Digital temperature display with high/low voltage protection
- Self-closing doors
- Robust handles on doors
- All underbars supplied with brake castors
- Dual thermopane safety glass used for glass doors
- Adjustable thermostat -14°C
- Auto Evaporation (The condensate is evaporated, hence no need to drain)
- All models are 220V Plug in and switch on











emd equipped™

Breakthrough technology replaces a conventional thermostat with an advanced electronic energy management system to cool quicker and maintain a more consistent temperature, while saving precious electricity.



green advantage™

By combining EMD control with ECM fans, electronic expansion valves and high-performance coils, we are able to further reduce energy consumption while improving cooling performance.



swift SWOp™

Our innovative swift l wop TM technology enables easy repalcement of the refrigeration deck without unpacking the contents of the fridge and without any skilled labour.



low e cabinet™

A superior combination of LED lighting, polyurethane insulation and low emissivity glass yields power savings around 40% lower than conventional refrigeration units.